

AMPHENOL Rugged Circular DIN Connectors Amphenol®



This product is RoHS compliant.

CIRCULAR DIN CONNECTORS, SERIES C091A

Features:

- Metal locking ring; screw locking according to DIN EN 60130-9/IEC 60130-9
- Internal metal strain relief with half shell construction and snap-in latching
- UL Approval File # E63093
- Complete EMI shielding in fully mated and locked position
- Solder termination
- Cable connector length: 2.658"
- Cable connector diameter: .670"




*Contact plating: silver unless noted with (Gold)


For quantities greater than listed, call for quote.

MOUSER STOCK NO.	Amphenol Part No.	Fig.	No. of Contacts	Voltage (IEC 60664-1)	Current (IEC 60512-3)	AWG Size	Price Each		
							1	10	50
Male Cable Connector, Max Cable O.D. is 6mm									
523-T3260-001	T 3260 001	A	3 DIN	300V	5A	20-26	299.84	275.19	253.97
* 523-T3300-018	T 3300 001	A	4 IEC	300V	5A	20-26	330.98	303.60	266.98
	T 3300 018	A	4 IEC	300V	5A	20-26	322.09	295.73	265.95
523-T3360-001	T 3360 001	A	5	300V	5A	20-26	307.71	282.38	260.82
* 523-T3360-018	T 3360 018	A	5	300V	5A	20-26	322.09	295.39	273.14
523-T3400-001	T 3400 001	A	6 DIN	300V	5A	20-26	334.41	306.68	283.07
523-T3475-001	T 3475 001	A	7	300V	5A	20-26	353.23	324.14	299.15
523-T3504-001	T 3504 001	A	8 DIN	100V	5A	20-26	325.51	298.13	275.88
523-T3635-001	T 3635 001	A	12	150V	3A	20-26	786.56	721.53	666.42
523-T3650-001	T 3650 001	A	14	150V	3A	24	738.98	719.81	622.27
Female Cable Connector, Max Cable O.D. is 6mm									
523-T3261-001	T 3261 001	B	3 DIN	300V	5A	20-26	381.98	350.49	308.05
523-T3301-001	T 3301 001	B	4 IEC	300V	5A	20-26	348.10	319.00	280.67
523-T3361-001	T 3361 001	B	5	300V	5A	20-26	357.00	327.56	302.23
523-T3401-001	T 3401 001	B	6 DIN	300V	5A	20-26	366.24	336.12	310.11
523-T3476-001	T 3476 001	B	7	300V	5A	20-26	406.63	372.74	344.68
523-T3505-001	T 3505 001	B	8 DIN	100V	5A	20-26	429.90	394.65	364.19
523-T3651-001	T 3651 001	B	14	150V	3.4	24	668.47	651.70	555.18
Female Panel Receptacle, Front Mounting									
523-T3263-000	T 3263 000	C	3 DIN	300V	5A	20-26	176.27	161.21	145.13
* 523-T3303-018	T 3303 000	C	4 IEC	300V	5A	20-26	178.33	163.61	144.10
	T 3303 018	C	4 IEC	300V	5A	20-26	223.85	205.71	186.20
523-T3363-000	T 3363 000	C	5	300V	5A	20-26	163.61	149.58	138.28
523-T3403-000	T 3403 000	C	6 DIN	300V	5A	20-26	182.44	167.72	154.37
523-T3478-000	T 3478 000	C	7	300V	5A	20-26	182.44	167.72	154.37
* 523-T3478-018	T 3478 018	C	7	300V	5A	20-26	243.70	236.86	209.13
523-T3507-000	T 3507 000	C	8 DIN	100V	5A	20-26	296.41	271.77	251.23
523-T3638-000	T 3638 000	C	12	150V	3A	20-26	534.30	490.83	452.84
523-T3653-000	T 3653 000	C	14	150V	3A	24	543.20	529.51	470.98
Male Panel Receptacle, Front Mounting									
523-T3262-000	T 3262 000	D	3 DIN	300V	5A	20-26	153.34	140.33	129.72
523-T3302-000	T 3302 000	D	4IEC	300V	5A	20-26	151.29	138.97	128.36
523-T3362-000	T 3362 000	D	5	300V	5A	20-26	159.84	146.50	135.54
523-T3402-000	T 3402 000	D	6 DIN	300V	5A	20-26	192.70	176.62	163.61
523-T3477-000	T 3477 000	D	7	300V	5A	20-26	179.35	164.64	151.63
523-T3506-000	T 3506 000	D	8 DIN	100V	5A	20-26	203.31	186.88	172.51


A




B




C




D




E



F



G



BAYONET LOCKING CIRCULAR DIN CONNECTORS, SERIES C091B

Features:

- Internal metal strain relief with half shell and snap-in locking
- UL Approval File # E63093
- Complete EMI shielding in fully mated and locked position
- Solder termination



For quantities greater than listed, call for quote.

MOUSER STOCK NO.	Amphenol Part No.	Fig.	No. of Contacts	Voltage (IEC 60664-1)	Current (IEC 60512-3)	AWG Size	Price Each		
							1	10	50
Male Cable Connector, Bayonet Locking Inside									
523-T3274-501	T 3274 501	E	3 DIN	300V	5A	20 - 26	202.97	185.86	167.72
523-T3324-501	T 3324 501	E	4 IEC	300V	5A	20 - 26	218.37	190.99	176.27
523-T3374-501	T 3374 501	E	5	300V	5A	20 - 26	218.03	199.55	184.83
523-T3424-501	T 3424 501	E	6 DIN	300V	5A	20 - 26	274.51	260.13	225.56
523-T3434-501	T 3434 501	E	7	300V	5A	20 - 26	225.22	206.39	190.99
523-T3524-501	T 3524 501	E	8 DIN	150V	5A	20 - 26	271.09	248.84	230.01
Female Cable Connector, Bayonet Locking Outside									
523-T3278-501	T 3278 501	F	3 DIN	300V	5A	20 - 26	254.31	233.78	210.16
523-T3328-501	T 3328 501	F	4 IEC	300V	5A	20 - 26	237.88	218.37	192.02
523-T3428-501	T 3428 501	F	6 DIN	300V	5A	20 - 26	425.80	390.88	360.76
523-T3438-501	T 3438 501	F	7	300V	5A	20 - 26	256.71	235.49	217.35
523-T3528-501	T 3528 501	F	8 DIN	150V	5A	20 - 26	326.19	298.81	276.22
Female Panel Receptacle, Bayonet Locking Outside, Rear Mounting									
523-T3277-100	T 3277 100	G	3 DIN	300V	5A	20 - 26	292.31	268.35	247.81
523-T3327-100	T 3327 100	G	4 IEC	300V	5A	20 - 26	320.03	293.33	270.74
523-T3377-100	T 3377 100	G	5	300V	5A	20 - 26	297.44	273.14	251.92
523-T3427-100	T 3427 100	G	6 DIN	300V	5A	20 - 26	314.21	288.20	265.95